Dart Aerospace Ltd. Tuesday, 8/21/2007 3:43:40 PM . 75 Kim Johnston **Process Sheet** : 02.250 SUPPORT : CU-DAR001 Dart Helicopters Services **Drawing Name** Customer Job Number 34188 12920 **Estimate Number** : D28911UP **Part Number** : NIA P.O. Number D2891 REV A1 This Issue : 8/21/2007 **Drawing Number** : N/A Project Number Prsht Rev. **Drawing Revision** First Issue : NA Material **Previous Run** : 9/20/2007 12 Um: **Due Date** Written By Checked & Approved By New Issue 07-07-04 JLM : Est Rev:A Comment **Additional Product** Job Number: Description: Seq. #: Machine Or Operation: **PURCHASING** 1.0 Comment: PURCHASING cho7/08/23 Issue P/O: Description: D6104-003 Material: 17-4 PH SS (AMS 5643 OR AISI 630) as per Dwg D6104 Material release note required. Blank size makes (2) D2891-1 17-4 SS Roundbar 3.25"OD D6104003 Comment: Qty.: 12.0000 Each(s) 1.0000 Each(s)/Unit Total: Support 2.25 dia PACKAGING RESOURCE #1 3.0 Comment: PACKAGING RESOURCE #1 Recieive & Inspect for Transit Damage Ensure Material Release Note is attached 4.0

MORI SEIKI

Comment: MORI SEIKI LATHE

5.0

Turn blank for Haas as per Folio FA046

INSPECT ALL DIM TO DIM SHEET



Comment: INSPECT ALL DIM TO DIM SHEET



Each

Dart Aerospace I	Ltd
------------------	-----

W/O:			✓ WORK ORDER CHANGES									
DATE	STEP	PRO	CEDURE CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector			
	~											
		· .	•									
Part No):	PAR #:	Fault Category:	NC	R: Yes	MO DQ N/C Close	A: <u>, </u>	Date:	<u> </u>			

NCR:		W	ORK OR	DER NON-CONFORMANCI	E (NCR)				
		Description of NC		Corrective Action Section B	Verification	Annessal	* * * * * * * * * * * * * * * * * * * *		
DATE	STEP		Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspecto
2/0/29	4.0	1 piece too short of .007	SP	Partacceptuble.	and		9		
) 41013			67. N.30		02/10/30		9.16.30 pu QSI UTZ	PA-10-30	
<u></u>			05/042			07/10/30	951042		
					,		٠		
						_			

NOTE: Date & initial all entries

Date: ' Tuesday, 8/21/2007 3:43:41 PM User: Kim Johnston **Process Sheet** Drawing Name: 02.250 SUPPORT Customer: CU-DAR001 Dart Helicopters Services Part Number: D28911UP Job Number: 34188 Job Number: Seq. #: Description: **Machine Or Operation:** HAAS CNC VERTICAL MACHINING #1 6.0 HAAS1 8. 5 or/11/17 d Comment: HAAS Machine as per Folio FA046 Tumble & Deburr INSPECT PARTS AS THEY COME OFF MACHINE 7.0 QC2 Comment: INSPECT PARTS AS THEY COME OFF MACHINE SECOND CHECK 8.0 QC8 Comment: SECOND CHECK PACKAGING RESOURCE #1 9.0 PACKAGING ' Comment: PACKAGING RESOURCE #1 Identify and Stock Location: FINAL INSPECTION/W/O RELEASE 10.0 Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



N 89.11.19

Dart Aerospace Ltd

W/O:			WORK OF	RDER CHANGES					
DATE	STEP	PROC	EDURE CHANGE	·	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
	;					N (c)	:		
				·	-				
Part No	:	PAR #:	_ Fault Category:	•	NCR: Yes	No DQA	Ä:	_ Date: _	
		•			QA:	N/C Closed	l:	_ Date: _	

NCR:	-	WORK ORDER NON-CONFORMANCE (NCR)						WORK ORDER NON-CONFORMANCE (NCR)					
		Description of NC		Corrective Action Section B		Verification	Amment	Ammana					
DATE	STEP	Section A	Initial Chief Eng	Action Description Significant Chief Eng	gn & Date	Section C	Approval Chief Eng	Approval QC Inspecto					
•						ļ							
							-						
						. *.	, .						
						:							
								-					
				·]									

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	34188
Description: Ø2.250 Support	Part Number:	D2891-1
Inspection Dwg: D2891 Rev. A1		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2891 Rev.A1/DSK076 Rev.A and record below:

Cauge Caug					Re	corded Actu	al Dimensi	ons		
A 2.274 2.279	Dim	Min	Max		1	2	3	4	Ву	Date
B 3.702 3.722 3.695 3.711 3.714 3.714 3.714 C 2.564 2.584 2.575 2.549 2.571 2.572 2.57					Lathe	Section				
B 3.702 3.722	A	2.274	2.279		2.277	2,278	2,276	2.277		
D 0.718 0.738 0.738 0.727 0.727 0.727 0.727 E 0.090 0.110 0.099 0.101 0.002 0.002 0.	В	3.702	3.722		3.695	3.711		3.714		
D 0.718 0.738 0.727 0.72	C .		2.584			2.569	2.571	2,572		
F 2.464 2.484	D		0.738		0.727	0.729	0.727		· .	
F 2.464 2.484	E		0.110		0.099	0.100	0.101			
G 2.029 2.049	F	2.464	2.484		2.477	2.470	2,476	2-476		
H 2.964 2.984	G		2.049			2035	2.033	2.035		
1	H					2.973	2.972	2.972		
J 0.022 0.042 0.033 0.032 0.032 0.032 0.032 0.099 0.090 0.095 0.055 0.058 0.055						0.921	0.922	0.927		
HAAS Section HAAS Section H	j				0.03		1.032	0.032		
HAAS Section AA 0.188 0.193 DT8706 0.129 187 188 188 188 188 188 189 189 189 189 189				***	0.099		0.099			
HAAS Section AA 0.188 0.193 DT8706 0.189 .187 .188 AB 0.240 0.260 0.250 .250 .249 .249 AC 0.115 0.150 0.125 .130 .127 .124 AD 0.040 0.060 0.055 .055 .058 .055 AE 0.010 0.020 0.010 .00 .00 .00 AF 0.240 0.260 0.250 .250 .250 .250 AG 0.290 0.310 0.298 .397 .290 .300 AH 0.115 0.150 0.138 .140 .H0 .40 AI 0.454 0.474 0.454 .499 .457 .470 AJ 2.779 2.789 2.782 2.783 2.783 2.783 2.782 AK 0.240 0.260 0.250 .250 .250 .250 AL 1.002 1.042 1.042 1.040 1.042 1.040 1.042 AM 0.053 0.073 0.063 .063 .063 AN 0.257 0.262 DT8683 0.258 .257 .257 .258 AN 0.253 0.073 0.063 .063 .063 AN 0.053 0.073 0.073 0.063 .063 .063					<u> </u>					
AB 0.240 0.260					HAAS	Section				
AB 0.240 0.260	AA	0.188	0.193	DT8706	0.189	,188	.184	.188		
AC 0.115 0.150	AB		0.260	111	0.250	250	,249			
AD 0.040 0.060	AC		0.150	1				.128		
AE 0.010 0.020	AD						058	.055		
AF 0.240 0.260	AE							,0(0		
AG 0.290 0.310 0.298 .397 .380 .300 AH 0.115 0.150 0.138 .140 .H0 .740 AI 0.454 0.474 0.4754 .489 .459 .470 AJ 2.779 2.789 2.783 2.783 2.783 2.783 2.782 AK 0.240 0.260 0.250 .250 .250 .250 AL 1.002 1.042	AF					.250	,250			
AH 0.115 0.150	AG			4		297	280	300		
AI 0.454 0.474	AH			1.	0.138			, 140		
AJ 2.779 2.789	Al						.459			
AK 0.240 0.260	AJ						2.783			
AL 1.002 1.042	AK									
AM 0.053 0.073 0.063 .063 .063 .063 AN 0.257 0.262 DT8683 0.258 .357 .257 .258 AO 1.663 1.683	AL			***						
AN 0.257 0.262 DT8683 0.258 .357 .257 .258 AO 1.663 1.683	AM			3 1						
AO 1.663 1.683	AN							.25-8		
AP 0.053 0.073 0.063 .063 .063 AQ 0.022 0.042 0.032 .032 .032 .032	AO						1.683	1,683		
AQ 0.022 0.042 0.032 0.32 0.32 0.32	AP						.063			
	AQ									
	AR	J.J			U. U = 3					
	AS	 								
Accept/Reject		Acc	ept/Reie	ct						

	_ 0.			
Measured by:	-Inc	125	Audited by	T.F.:
Date:	07/10/30	107/4/13	Date:	07/11/18

Rev	Date	Change	 Revised by	Approved
Α	02.12.12	New Issue	KJ/RF	#-

DART AEROSPACE LTD	Work Order:	34188
Description: Ø2.250 Support	Part Number:	D2891-1
Inspection Dwg: D2891 Rev. A1		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2891 Rev.A1/DSK076 Rev.A and record below:

			grited on mape	1		ıal Dimensi	ons		
Dim	Min	Max	Go/No Go Gauge	1.5	26	27	x8	Ву	Date
Lathe Section									
Α	2.274	2.279		2277	2,277	2.278	2,277		
В	3.702	3.722	,	3.714	3.714	3.7/2	3.712		
С	2.564	2.584		2,573	2.573	2,574	2.574		
D	0.718	0.738		6.727	0.726	0.726	0.726		1.2
E	0.090	0.110		0.101	0.101	0,100	0.100		
F	2.464	2.484		2.477	2.476	2.477	2,477		
G	2.029	2.049		2.035	2.035	2.034	2,032		
Н	2.964	2.984		2,973	2.973	2,974	2.972		
·	0.913	0.933	٠,	0.925	0.927	0.927	0.929		
J	0.022	0.042		0.032	0.032	0.032	0.032		
K	0.090	0.110		0.099	0.099	0.100	0,100		
L									
		<u></u>		HAAS	Section				
AA	0.188	0.193	DT8706	.188	188	.184	188		
AB	0.240	0.260		.252	.250	258	.255		
AC	0.115	0.150		1128	.128	-127	.122		
AD	0.040	0.060		058	.058	1058	060		
AE	0.010	0.020		015	,015	-015	2015		
AF	0.240	0.260		,240	.240	.240	.740		
AG	0.290	0.310		.300	,300	.300	,300		
AH	0.115	0.150		.180	140	140	.140		
ΑI	0.454	0.474		.460	.460	.460	,460		
AJ	2.779	2.789		2.782	,2. KI	2.78	2-782		
AK	0.240	0.260		250	.750	,250	,200		
AL	1.002	1.042		1.040	1.040	1.040	1.040		
AM	0.053	0.073		.063	-063	.063	JOS 3		
AN	0.257	0.262	DT8683	.258	, 258	,258	,258		
AO	1.663	1.683		1.683	1-683	1681	1.681		
AP	0.053	0.073		. 263	. 063	,063	,063		
AQ	0.022	0.042		.032	,632	.032	,032		
AR									
AS									
	Acc	ept/Reje	ct						

Measured by:	Audited by J.F.
Date: 62/16/36	Date: 07////8

Rev	Date	Change	Revised by	Approved
Α	02.12.12	New Issue	KJ/RF	#


DART AEROSPACE LTD	% Work Order:	34188
Description: Ø2.250 Support	Part Number:	D2891-1
Inspection Dwg: D2891 Rev. A1		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2891 Rev.A1/DSK076 Rev.A and record below:

				Red	All 1				
Dim	Min	Max	Go/No Go Gauge	2.9	2118	211	12/2	Ву	Date
				Lathe	e Section				
Α	2.274	2.279		2.278	2.277	2.278	2,279		
В	3.702	3.722		3.712	3.712	3.712	3.714		
С	2.564	2.584		2,574	2.574	2.574	2.574		
D	0.718	0.738		0.727	0.727	0.726	0,727		
E	0.090	0.110	-	0.101	0.100	0,101	2.477		J. 10
F	2.464	2.484		2.47	2,478	2.477	2.477		
G	2.029	2.049		2,035	2.033	2.034	2.033		
Н	2.964	2.984	····	2.973	2.473	2.973	2.973		
1	0.913	0.933		0.923	0.927	0.925	0.972		
J	0.022	0.042	•	0.032	0.032	0.032	0.032		
K	0.090	0.110		0.100	0.100	0.100	0.106		
·L			,						
	<u> </u>			HAAS	Section				
AA	0.188	0.193	DT8706	.188	.184	188	. 188		
AB	0.240	0.260		.255	,250	259	258		
AC	0.115	0.150		128	127	:127	127		
AD	0.040	0.060		.055	055	-258	1053		
AE	0.010	0.020		-015	.015	,015	1015		
AF	0.240	0.260		250	250	,250	,250		
AG	0.290	0.310		. 300	- 300	.290	. 290		
AH	0.115	0.150	· · · · · · · · · · · · · · · · · · ·	140	-140	-145	-140		
ΑI	0.454	0.474		, 460	.460	,463	- 460		
AJ	2.779	2.789		2 780	2780	2.780	2-780		
AK	0.240	0.260		250	-250	1250	.250		
AL	1.002	1.042		1.040	1.040	1.039	1,038		
AM	0.053	0.073		063	·053	.063	.063	`	
AN	0.257	0.262	DT8683	25-7	-257	.257	~257		
ΑO	1.663	1.683		1.680	1.680	1.692	: 1582		
AP	0.053	0.073		,063	.063	1063	.063		· 64
AQ	0.022	0.042		,032	.03Z	,032	.032		= x .
AR		··-			,				
AS									
	Acc	ept/Reje	ct						

- A	
Measured by:	Audited by T.F. 07/1//8
Date: 07/0/30	Date:

Rev	Date	Change	Revised by	Approved
Α	02.12.12	New Issue	KJ/RF	#





DA BAY 077

	ICIDIO ICIGITY In of Crucine Measure's Corporal	SYF	ACUSE V YORK 1320	, ,	C	ERT	IFIC/	ATE	OF T	ES	•	
s A M CAST	LE, THE		•	SHI	A H	CAS ILE	L. Year				FU-LI33	
D 3400 N W T FSANKLIN	CLF AD FARK, I	<u>ျ</u> ဆိ	5131	7 0	2680 BEDF	C MILE ORD HE	ES RD EIGHTS :	OM 4414	ó	្ប	0//15/ غ//15/	ATE 107
CUSTOMER ORG		cu	STOMER REQ.	* DISTRICT		B FA	SSONS		SHIPPED FROM		SYRACUSE	
AMC-3174 AMS-5643	IPH RT A I-10 REV IG AISI	7 630	ASME-5A	17400		30 <u>.</u> - 1						
HEAT NO.						CHEMIC	CAL ANÁLYSIS					
A18939	0 .037	MN .42	.027	.022	3I .63	HI 4.09	CR 15.28	#0 •11	€0 3.22	. 29		

CASTLE METALS CORP. DATE RCVD APPROVED BY

MECHANICAL PROPERTIES HEAT NO. QUANTITY BEDZAREAX HARDNESS XEL ONG GO TENSILE PSI YLD.2%FAI 1814 # A18737 EHN 356 3C 35 CAPABILITY PHYSICALS AFTER 900 DEG. F. - 1 HR. AIRCOGL: ELA MHG 51.1 174,050 12.3 203,000 MACRO TEST OR FERRITE 5 %


MAGNAFLUX F/S = 0/0

REBUCTION RATIO: 27.5:1 MATERIAL SOLUTION TREATED AT 1900 DEG. F. HELD 45 MINUTES AT TEMPERATURE -AIRCOGLED.

CAUCIBLE MATERIALS CORF. VENDOR \$15410. HATERIAL INGGT CAST. MAFTA - YES

THANK YOU FOR SELECTING A QUALITY PRODUCT MATERIAL FREE FROM MERCURY CONTAMINATION AT TIME OF SHIPMENT MANUFACTURED BY THE EMPLOYEES OF CRUCIBLE SPECIALTY METALS NO WELD REPAIR PERFORMED MATERIAL MELTED IN U.S.A. THE ABOVE MATERIAL WAS MANUFACTURED AND TESTED IN COOR

THE THIS			WITH ABOVE SPECIFICATIONS AND IS IN CONFORMANCE WITH SPECIFICATION REQUIREMENTS.
SWORN TO AND SUBSCRIBED BEFORE ME THIS	•		COLICIDI & MATERIAI & CORPORATION
20		n ,	ACTING BY AND THROUGH ITS SPECIALTY METALS DIVISION
DAY OF, 20			11-7.64116
		CERTIFIED	11-1,0000
	•	BY:	QUALITY ASSURANCE REPRESENTATIVE
NOTARY PUBLIC			



P.O. BOX 977 SYRACUSE NEW YORK 13201

CERTIFICATE OF TEST

	A Greater of Cruatio Manual Congruency	NEW YORK 13201	OLITI		O , 1	
	4 M CASTLE: INC		S A H CASTL	E. IND.	• • •	FS-LL330
) D T	3460 N WELF RD FRANKLIN FARK, IL	50131	P 26800 MIL T BEDFORD H	ES RD EIGHTS OH 44.	(46	0//16/0
	CUSTOMER ORDER # & DATE	CUSTOMER REQ.	DISTRICT B FA	RSONS	SHIPPED	SYRACUSE
OE	CRU 17-4PH RT A AMC-3174-10 REV 7 AMS-56430 AISI		And the second of the second o	SIZE 3.250 RD 4STH -A S64-04	T630	•
<u>,</u>			CHEMI	CAL ANALYSIS		
HE	A18939 C .037	MN P .42 .027 .	5 SI NI 022 .63- 4.09	CR 20 15.28 .41		TA .012
				DATE RC	LE METALS CO VD 7/25/ 2-17-0 ED BY 4	
QI.	ANTITY HEAT NO.		MECHANI	CAL PROPERTIES		
-	LS14 # ALS939 CAPABILI MACRO TEST OR FERRITE 5 % MAGNAFLUX F/S = 0	TY PHYSICALS 203.000	PSI YLD.2%F5I AFTER 900 DEG. 174.090	ZELONG45 F 1 88. f 12.3	SEDVAREAX STRCOOL: 51,1	HARDNESS BHN 356 30 38 BHN 415
*	REDUCTION RATIO: MATERIAL BOLUTION AIRCOOLED.	27.511 TREATED AT	1900 DEG. F. HE	LD 45 HINUTES	S AT TEN	IPERATURE
	CAUCIBLE MATERIAL MATERIAL INDOT CA MARTA - YES	.5 CORF. VEND Yer.			: :	
- 1	WATERIAL FREE FROM MERCURY CO NO WELD REPAIR PERFORMED MATERIAL MELTED IN U.S.A.	NTAMINATION AT TIME OF	F SHIPMENT THANK 1 BY THE EMPLOYE	YOU FOR SELEC ES OF CRUCIE	iting a qua Le speciali Managatur	Y MEINLS
	SWORN TO AND SUBSC	RIBED BEFORE ME	, 20 CER	WITH ABOVE SPE SPECIFICATION RE CRUC ACTIN TIFIED	CIFICATIONS AND IS RIPERMENTS. ISSUE MATERIALS CORPO IG BY AND THEOLIGH ITS	IN CONFORMANCE 1